



ELECTRONIC HOOTER (MODEL: Q -100H)



ELECTRONIC HOOTER/ BUZZER/ BELL

Specification:

Sound: Hooter : Intermittent sound
 Buzzer: Continuous sound
 Bell : Electric Bell sound

Supply voltage: 20 to 300V DC – universal voltage

Optional : 12V DC along with universal voltage

Sound dB : 90 dB at 1meter

Tone : Fixed tone (Factory set)

Panel cutout : 92 x 92 mm

Front size : 96 x 96 mm

ELECTRONIC HOOTER WITH ACCEPT PUSH BUTTONS

Specification:

Sound: Intermittent sound

Supply voltage: 20 to 300V DC – universal voltage

Sound dB : 90 dB at 1meter

Tone : Fixed tone (Factory set)

Panel cutout : 92 x 92 mm

Front size : 96 x 96 mm

Sound Accept by : Inbuilt push button



ELECTRONIC HOOTER WITH OUTPUT CONTACTS

Specification:

Sound : Intermittent sound

Supply voltage: 12 TO 40V DC

Sound dB : 90 dB at 1meter

Tone : Fixed tone (Factory set)

Panel cutout : 92 x 92 mm

Front size : 96 x 96 mm

Inbuilt output contact – 1NO potential free contact for remote application